



<< NOTE >>

1. WEIGHT : 6.5Kg
2. IP GRADE : IP 56
3. INSTALLATION POSITION : BRIDGE WING ( P & S )
4. PAINTING COLOR : MUNSELL NO. 7.5BG 7/2
5. RUDDER ANGLE :  40°  45°  50°  65°  70°

6	CABLE GLAND	BRASS	1	<input type="checkbox"/> 20a <input type="checkbox"/> 20b <input type="checkbox"/> 20c <input type="checkbox"/> 25a <input type="checkbox"/> 25b <input type="checkbox"/> 25c	13	EARTH BOLT	BRASS	1	
5	TERMINAL COVER	ALDC	1		12	BODY	ALDC	1	
4	NAME PLATE	SUS	1		11	DIMMER SWITCH		1	0.6W 200KΩ / RV30Y
3	TERMINAL	PHENOL	1	6P	10	ILLUMINATION	LED PLATE	1	
2	SYNCHRO MOTOR		1	<input type="checkbox"/> TS5N2E11 <input type="checkbox"/> TS5N2E12	9	INDICATOR DIAL	ACRYL	1	
1	NEEDLE	ACRYL	1		8	COVER	ALDC	1	
					7	DIMMER CASE	ALDC	1	
NO.	NAME OF PARTS	MATERIAL	Q'TY	REMARKS	NO.	NAME OF PARTS	MATERIAL	Q'TY	REMARKS
SCALE	N / S	APPROVED	B.U.YANG		TITLE <b>INDICATOR</b>				
UNIT	mm	CHECKED	Y.G.PARK						
METHOD		DRAWN	S.M.RYU						
					REVISION	MODEL	SD-200	DWG. NO.	DIC-RI-32200
					0 (1) 2 3	DATE	2008.12.01	SHEET NO.	7